












	<b>Model</b>	<b>IsyTech 36-12D</b>	
	<b>Code Production</b>	917171	
Interface :			
			
	<b>Overall Dimension (Width-Depth-Height) *open</b>	mm	575x605(1005*)x820
	<b>Packaging Dimension (WxDxH)</b>	mm	690x670x980
	<b>Gross weight</b>	Kg	62
	<b>Net weight</b>	Kg	56
	<b>Volume</b>	mc	0,45
	<b>Rack size</b>	mm	500x500
	<b>Max door /hood opening</b>	mm	365
	<b>Max glasses/plate Height</b>	mm	325
	<b>General construction</b>		single skin
	<b>Door/hood Construction</b>		double skin
	<b>Tank construction</b>		welded
	<b>Tank volume</b>	liter	20
	<b>Tank heating element</b>	W	1.400
	<b>Tank surface strainers</b>		composite
	<b>Wash pump type</b>		double flow
	<b>Wash pump power</b>	W	470
	<b>Wash temperature</b>	°C	60 (45-->70)
	<b>Boiler type</b>		without pressure
	<b>Boiler volume</b>	liter	6
	<b>Back-flow system</b>		break tank
	<b>Boiler heating element</b>	W	4.900
	<b>Rinse booster pump</b>		YES
	<b>Rinse booster pump power</b>	W	200
	<b>Rinse temperature</b>	°C	80 (60-->88)
	<b>Rinse water consumption</b>	Liter /rack	1,8
	<b>Optimal external water pressure</b>	bar	1 - 4
	<b>Drain system</b>		overflow
	<b>Drain filter</b>		double filtering
	<b>Drain pump</b>		optional
	<b>Rinse aid dispenser</b>		YES
	<b>Detergent dispenser</b>		YES
	<b>Wash cycle</b>	sec	60 - 90 - 180
	<b>Special cycle</b>	programs	n°6
	<b>Self cleaning cycle</b>		YES
	<b>Electric Power</b>	W	6.800
	<b>Electric Connection</b>	V - ph - Hz	400V 3N 50Hz
	<b>Fuse</b>	A	16
	<b>Water softner</b>		NO
	<b>Plates racks</b>	N°1	780131
	<b>Flat Rack</b>	N°1	780132
	<b>Cutterly Rack</b>	N°1	780139
	<b>Electric cable</b>		YES
	<b>Drain hose</b>		YES
	<b>Fill hose</b>		YES

