



More Info

Data sheet



## ZUB 4 wells - handle face side

The mobile serving system.

The robust stainless steel trolley with four separately controllable, electrically heated GN 1/1 heated wells is used for the safe transport, distribution on the conveyor and serving of food in a GN system. The universal delivery trolley for the best food quality at distribution stations. Can be heated reliably wet and dry; dry heating provides significant energy savings and less cleaning of the wells is required.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid.

The functions can be customised to suit the requirements, with a gantry (lighting/heat), a hinged shelf on the long/face side, as well as a hinged work surface on the face side. An additional usable work surface in the substructure also provides space for thermoport® 50 and 100 transport boxes for the immediate refilling of food in a GN system thanks to the stable shelf.

For a complete solution on a food distribution conveyor in combination with other mobile products, such as the thermoport® made of plastic and stainless steel, various dispensers, tray and banquet trolleys as well as transport and serving trolleys.







## TECHNICAL SPECIFICATIONS

ZUB 4 wells - handle face side





88 16 04 01



## TECHNICAL SPECIFICATIONS

| Dimensions        | 1520 x 678 x 900 mm          |
|-------------------|------------------------------|
| Material          | stainless steel 1.4301 (CNS) |
| Weight            | 54,9 kg                      |
| Connected load    | 1.880 W                      |
| Rated voltage     | 1N AC 230 V 50/60 Hz         |
| Plug type         | Safety switch (type F)       |
| Cable length      | 2.500 mm                     |
| Heating Area      | +30°C to +110°C              |
| Protection class  | IPX4                         |
| Impact protection | 4 corner bumpers             |
|                   | 2 fixed-; 2 swivel castors   |
| Castor            | with brakes                  |
| Castor type       | Rustproof                    |
| Wheel diameter    | 125 mm                       |
| GN depth          | 200 mm                       |
|                   |                              |

## BENEFITS

Rustproof, high-quality, hygienic stainless steel.

Rounded worktop, turned down all-round, protection against the ingress of dirt/water.

Deep-drawn heated well, seamlessly welded.

Insulated on all sides, low heat loss.

Mobile with robust, fixable castors and a pushing handle.

Corner bumpers for impact protection as well as a shockproof switching element.

Integrated drainage cock, quick and easy cleaning.

Order number